## - 2 -

## IN THE SPECIFICATION

At page 6 from line 9 through line 23 please amend the specification as follows:

The release compositions of the present invention comprise additives for improved anchorage of release coatings comprising the reaction product

of:

- 1)  $R^{E_h}Si(OR^A)_{3-h}$   $R^{E_h}Si(OR^A)_{4-h}$ ;
- 2)  $R^{v_i}Si(OR^B)_{3\underline{4}-i}$

 $S(\mathcal{L}^{\mathcal{B}})$  A catalyst; and

4) water

where R<sup>E</sup> is an oxirane or epoxide containing radical having from one to forty carbon atoms, R<sup>vi</sup> is selected from the group consisting of two to forty carbon atom terminal olefinic monovalent hydrocarbon radicals, R<sup>A</sup> is selected from the group consisting of one to forty carbon monovalent hydrocarbon radicals; R<sup>B</sup> is selected from the group consisting of one to forty carbon monovalent hydrocarbon radicals, where h varies from 1 to 3 and where i varies from 1 to 3. The preferred catalysts are either an organo tin or organic acid such as formic acid.

At page 9 from line 5 through line 19 please amend the specification as follows:

The release compositions of the present invention comprise additives for improved anchorage of release coatings comprising the reaction product

 $\alpha$ 

of: SUB

- 1)  $R^{E_h}Si(OR^A)_{34-h}$ ;
- 2) RviiSi(ORB) 43-i;

3) A catalyst; and

4) water

where R<sup>E</sup> is an oxirane or epoxide containing radical having from one to forty carbon atoms, R<sup>vi</sup> is selected from the group consisting of two to forty carbon atom terminal olefinic monovalent hydrocarbon radicals, R<sup>A</sup> is selected from the group consisting of one to forty carbon monovalent hydrocarbon radicals; R<sup>B</sup> is selected from the group consisting of one to forty carbon monovalent hydrocarbon radicals, where h varies from 1 to 3 and where i varies from 1 to 3. The preferred catalysts are either an organo tin or organic acid such as formic acid.

At page 10 line 15 through page 11 line 3 please amend the specvification as follows:

The release compositions of the present invention comprise:

(A) additives for improved anchorage of release coatings comprising the reaction product of:

5UB

- 1)  $R^{E}_{h}Si(OR^{A})_{3\underline{4}-h};$
- 2) RviSi(ORB) 34-i;

- A catalyst; and
- 4) water

where R<sup>E</sup> is an oxirane or epoxide containing radical having from one to forty carbon atoms, R<sup>vi</sup> is selected from the group consisting of two to forty carbon atom terminal olefinic monovalent hydrocarbon radicals, R<sup>A</sup> is selected from the group consisting of one to forty carbon monovalent hydrocarbon radicals; R<sup>B</sup> is selected from the group consisting of one to forty carbon monovalent hydrocarbon radicals, where h varies from

Q3

- 4 - 60SI01998

1 to 3 and where i varies from 1 to 3; the catalyst can be either an organo tin or formic acid and coating compositions comprising: